



**NEW
PRODUCT**

ENVIRO-DUO-EX

Recovery Station
Two-Piston



BENEFITS

- Suitable for refrigerants of class A1, A2, A2L, A3
- ATEX-certified device II 3G Ex ec ic nC h IIA T4 Gc
- Oil-free and maintenance-free compressor
- Equipped with overfill protection (80%) and self-cleaning mode



Part No
4689021

DISCOVER
THE PRODUCT
ONLINE



REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally



DATA SHEET

Property	Value
Electrical ratings	220 – 240 V / 50 Hz / 60 Hz
Current	6 A
Motor	0.75 kW (1 HP)
Recovery Rate	Vapour rate: up to 20.4 kg/h (45 lb/h) Liquid rate: up to 393 kg/h (866 lb/h) Push-pull: up to 501 kg/h (1'105 lb/h) for R410A
High pressure protector	38,5 bar (558.4 psi)
Rotational speed	3000 rpm
Number of pistons	2
Noise level	70 dB(A)
Connector A	1/4" SAE
Connector B	1/4" SAE
Operating temperature	0 °C – 40 °C (32 °F – 104 °F)
Ingress protection	IP20
Protection class	I
Dimensions	420 x 260 x 315 mm (16.5 x 10.2 x 12.4")
Weight	12.8 kg (28.2 lb)