



**NEW
PRODUCT**

FLARE-e

Electronic Flaring Tool



BENEFITS

- Precise and fast 45° flaring
- High-performance battery
- Lightweight and compact
- Maximum safety: flaring clamps are lockable. FLARE-e starts only with the clamp installed
- Suitable for metric and imperial flaring clamps

FLARE-eZ (imperial) Part No 4689045

FLARE-eM (metric) Part No 4689142

DISCOVER
THE PRODUCT
ONLINE



REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally



DATA SHEET

Property	Value
Flaring of the tubes	45° flaring
Voltage	12 V
Capacity	2500 mAh
Frequency of tube expansion	Up to 135 times (fully charged battery)
Operating temperature	5 °C – 40 °C (41 °F – 104 °F)
Storage temperature	-20 °C – 60 °C (-4 °F – 140 °F)
Dimensions	242 x 102 x 90 mm (9.5 x 4 x 3.5")

Spare parts and accessories:

FLARE-e-Case	4689060
RFA-209-STYLO-HD	4687051
REFCO 12V 2.5 Ah Li-Ion Battery	4689058
REFCO 12V Charger	4689059
Flaring Clamp 1/4"	4689061
Flaring Clamp 5/16"	4689062
Flaring Clamp 3/8"	4689063
Flaring Clamp 1/2"	4689064
Flaring Clamp 5/8"	4689065
Flaring Clamp 3/4"	4689066
Flaring Clamp 6mm	4689067
Flaring Clamp 8mm	4689068
Flaring Clamp 10mm	4689069
Flaring Clamp 12mm	4689070
Flaring Clamp 16mm	4689071
Flaring Clamp 19mm	4689072