NEW PRODUCT

DETECTOR-CO2

Leak detector



BENEFITS

- Detects even the smallest CO_2 leaks
- Quickly locates leaks with three easily adjustable sensitivity levels
- Simple and intuitive operation
- Flexible power supply (battery and USB)

Part No
4689099

DISCOVER THE PRODUCT ONLINE

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally

DATA SHEET

Property	Value		
Minimum sensitivity	3 g/a / 0.1 oz/a		
Sensor Lifetime	Approx. 10 years with proper use and regular filter replacement		
Sensitivity levels	High 3 g/a	Medium 15 g/a	Low 30 g/a
Display	4-colour LCD-Display		
Operating temperature	-10 °C – +50 °C / +14 °F – +122 °F		
Storage temperature	-20 °C – + 60 °C / -4 °F – 140 °F		
Power supply	4 x 1.5 V AA batteries		
Alternative power supply	Micro USB		
Probe length	40 cm / 16“		
Auto shut off	After 10 minutes without pressing a button		
Humidity range	0–90% relative humidity (non-condensing)		
Dimensions	260 mm x 78 mm x 48 mm / 10.24“ x 3.07“ x 1.89“		
Weight	418 g / 0.92 lb		

Spare parts and accessories:

CO2-LOCATOR-FILTER/2
Spare Filter for CO2-LOCATOR, 2 pcs 4688016

REFCO Manufacturing Ltd.
Hitzkirch – Suisse

Acknowledged globally