NEW PRODUCT

ECO-5-EX

Two stage vacuum pump



BENEFITS

- ATEX-certified device
- Suitable for A2L, A2 and A3 refrigerants
- Fast and reliable evacuation to a deep vacuum
- Lightweight and compact
- ATEX-certified solenoid valve main tains the vacuum in the event of a power failure

Part No
4689475

DISCOVER THE PRODUCT ONLINE

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally

DATA SHEET

Property	Value
Motor	0.37 kW / 1/2 HP
Voltage	230 V
Flow rate	142 l/min / 5 CFM
Final vacuum	15 micron
Frequency	50 Hz / 60 Hz
Rotational speed	2850 rpm
Intake port	1/4“ SAE and 3/8“ SAE
Oil capacity	460 ml / 15.6 oz
Ingress Protection	IP20
Protection class	I
Operating temperature	-1 °C to 40 °C
Storage temperature range	-10 °C to 40 °C
Dimensions	340.5 × 139 × 254.3 mm
Weight	12.62 kg

Spare parts and accessories:

DV-46-Y (Vacuum Pump Oil, 1 l)	4495323
VCL-60-3/8“SAEx1/4“SAE (Vacuum Hose)	4688477
REFVAC-RC (Wireless Digital Vacuum Gauge)	4688291

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally