NEW PRODUCT

INVERTER CHECKER

Inverter Diagnostic Tool



BENEFITS

- Fast and easy diagnosis of inverter systems
- Automatic testing – no continuous monitoring required
- Stored test results can be accessed at any time
- Compact and lightweight

Part No
4689535

DISCOVER THE PRODUCT ONLINE

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally

DATA SHEET

Property	Value
Operating temperature	-20 °C – 70 °C
Storage temperature	-30 °C – 70 °C
Operating humidity	0 – 90 %
Operating altitude	Max. 4000 m (13123 ft)
Battery type	2 × AAA (alkaline)
Protection rating	IP44
Connection terminals	3 × Ø 4 mm banana sockets
Input signal frequency	3 – 20000 Hz
Input voltage range	105 – 600 V DC (inverter test mode) 20 – 50 V DC (data bus test mode)
Operating time	> 40 hours
Phase current	Max. 9 mA
Assigned insulation of external circuit	CAT II 600 V, pollution degree 2, Class 2
Dimensions	50 × 155 × 24 mm (2.0 × 6.1 × 0.9 in)
Weight	164 g (including batteries)

Spare parts and accessories:

IC-POUCH (Pouch)	4689492
IC-BATTERY-COVER + O-Ring (Battery cover)	4689453
IC-CROC-CLIP/3 (Crocodile clips)	4689675

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally