NEW PRODUCT

REFMASTER

Digital Manifold



BENEFITS

- One-handed operation thanks to its slim design
- Intuitive menu navigation through every step of the process
- Large 5-inch TFT touchscreen for a clear overview
- Wireless connectivity with other REFMESH devices
- Automatic energy optimisation when used with REFTUNE

Part No
4689700

DISCOVER THE PRODUCT ONLINE

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally

TECHNICAL DATA

Property	Value
Display	5“ TFT-Touchdisplay
Pressure range	-0.95 to +60 bar
Overpressure	150 bar
Pressure accuracy	±0.25 % FS
Ingress protection	IP54
Connections, 2-way manifold	4 × 1/4“ SAE (7/16 UNF-20),
Connections, 4-way manifold	4 × 1/4“ SAE (7/16 UNF-20), 1 × 3/8“ SAE
Communication interfaces	BLE, USB-C
Bluetooth range	Up to 300 m
Battery	LiPo, 8500 mAh
Supported refrigerants	Over 100 refrigerants (free update)
Temperature measurement range	-40 to +125 °C
Temperature accuracy	±1 K
Operating temperature	-20 to +50 °C
Humidity range	0–90 %, non-condensing
Storage temperature range	-40 to +60 °C
Dimensions, 2-way / 4-way	190 × 100 × 66 mm / 190 × 100 × 78 mm
Weight, 2-way / 4-way	1.06 kg / 1.21 kg

REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally