



**NEW
PRODUCT**

REFVALVE

Refrigerant Switching Valve

BENEFITS

- Wireless connection of RESCALE-S, and REFMATE with REFVALVE
- Charging to target weight
- Failsafe operation: automatic closure when system is turned off
- Very low energy consumption due to bi-stable valve
- Suitable for all refrigerants up to 580 psi



REFMESH
DIGITAL REPORTING

Part No
4689024

DISCOVER
THE PRODUCT
ONLINE



REFCO Manufacturing Ltd.
Hitzkirch – Switzerland

Acknowledged globally



DATA SHEET

Property	Value
Maximum working pressure	40 bar (580 psi)
Communication interface	BLE
Connectors	2 x 1/4" SAE
Battery type	4x AAA
Operating hours	>40 hours or >4'000 switching cycles
Signal range	100 m (330 ft)
Ingress protection	IP54
Operating temperature	-20 °C – 50 °C (-4 °F – 122 °F)
Storage temperature	-40 °C – 60 °C (-40 °F – 140 °F)
Dimensions	77 x 134 x 50 mm (3 x 5.3 x 2")
Weight	550 g (1.2 lb), batteries included

Spare parts:

REFVALVE-BATT-COVER+O-RING	4689190
REFVALVE-POUCH	4689042
CL-12-B-OD-MONTAGE	4689183